VIKING PUMP°








724 SERIES™, 4724 SERIES™

STAINLESS STEEL CONSTRUCTION | UNIVERSAL PRODUCT LINE



FEATURES & BENEFITS

- Cast iron mounting bracket lowers overall pump cost (316SS wetted parts)
- Behind the rotor mechanical seal eliminates the shaft and bushing from being exposed to media
- I Jacketed bracket provides the ability to maintain uniform temperature to sealing area



* Mechanical seal is in stuffing box only.










PERFORMANCE

MODELS		SPECIFICATIONS				
Jacketed		Performance			Standard Ports	
Packing	Behind the Rotor Seal	Max Speed, RPM	GPM	m³/h	Size, Inches	Туре
F724*	F4724*	1750	1.5	0.3	0.5	NPT
FH724*	FH4724*	1750	3	0.7	0.75	NPT
G724*	G4724*	1150	5	1	1	NPT
H724	H4724	1750	10	2.3	1.5	NPT
HL724	HL4724	1750	20	4.5	1.5	NPT
K724	K4724	520	45	10	2	NPT
KK724	KK4724	520	65	15	2	NPT
L724	L4724	420	90	20	2	NPT
LQ724	LQ4724	420	90	20	2.5	Flange
LL724	LL4724	420	110	25	3	Flange


^{*} Stuffing box seal, non-jacketed

CURVES

NON-JACKETED



JACKETED



PORTING

- Right Angle (90°) (Rotatable Casing), H-LL
- Opposite (180°) (Rotatable Casing), F-G
- INPT/BSP
- I Flanged (ANSI)

SEALING

- Packing
- Component Behind the Rotor Mechanical Seal, H-LL
- Component Mechanical Seal in Stuffing Box, F-G

MOUNTING

Foot Mount

(K724 R Drive)

DRIVES

- Offset Gear Reducer Drive
- Purchased Gear Reducer Drive
- Direct-Mounted Drive
- V-Belt Drive

TYPICAL APPLICATIONS

- Soaps, Detergents
- & Surfactants Acids & Caustics
- Water-based Liquids
- I Vegetable Oil
- I General Chemicals

VIKING PUMP, INC. A Unit of IDEX Corporation 406 State Street

Cedar Falls, Iowa 50613 U.S.A.

vikingpump.com

CONTACT YOUR STOCKING DISTRIBUTOR TODAY

